



Sales Catalog of HNK Telecommunication Products

Fiber Optic Cable Termination Box

Fiber Optic Cable Termination Box Series

Fiber Optic Cable Termination Box series are designed for use in residential and business applications, we offer a wide range of different termination boxes for all adapter types which provides a flexible solution to the user. The units can be quickly installed within an office, house or communication room environment.

Standards Compliance

- TIA/EIA 568.C, Optical Fiber Cabling Components Standard.
- IEC61754, Fiber optic connector interfaces Standard.
- ANSI/TIA/EIA-606-A (Administration Standard for Telecommunications Infrastructure.)
- GR-449-CORE (Generic Requirements and Design Consideration for Fiber Distributing Frames.)
- UL 94 (Tests for Flammability of Plastic Material for Parts in Devices and Appliances.)
- RoHS (Directive on Restriction of Hazardous Substances.)

Features

- Fiber Optic Termination Boxes are light and compact whilst maintaining adequate fiber storage needs and minimum bend radii.
- Termination Boxes can be wall or pole-mounted and have a variety of core capacities and adapter types available.

Ordering Information

Using the available configurations amend/create product codes using the formula below.

Part Number: XX-AA-BBC-(DCLEF)

Ordering Guide

XX	Termination box Type	PTB =Plastic Termination box, MTB =Metal Termination box
AA	Product ID	please see the reference below
BB	Port Capacity	01 =1 Port, 04 =4 Ports, 16 =16 Ports
C	Configuration	E =only Termination box, L =With Adapters, F =With Adapters and Pigtails
D	Adapter Connector Type	FP,SP,SA,LP
CL	Adapter Color(CL)	BL /Blue for Singlemode PC Standard, BG /Beige for Multimode Standard, AQ /Aqua for OM3 Standard, GR /Green for Singlemode APC Standard and PU /Purple for OM4 Standard (Metal Structure Unsuitable)
E	Fiber Type	OM1 =62.5/125 OM1, OM2 =50/125 OM2, OM3 =50/125 OM3, OM4 =50/125 OM4, G652D =9/125 G652D, G657A =9/125 G657A
F	Fiber Length	05 =0.5M, 10 =1M

Adapter Connector Type Code

Code	Connector	Code	Connector	Code	Connector	Code	Connector
FP	FC/PC	FA	FC/APC	LP	LC/PC	LA	LC/APC
SP	SC/PC	SA	SC/APC	TP	ST/PC	TA	ST/APC

Sales Catalog of HNK Telecommunication Products
Fiber Optic Cable Termination Box

1 ~ 4 Fibers Termination Box (PTB012)

PTB012 termination box is designed for use in FTTX network applications for the termination of up to 4 fibers. It incorporates a hinged tray for fiber management and a removable cover for easy access. The capacity of this box can be 1 core, 2 cores and 4 cores.



Product Features

- Excellent ergonomics design, graceful appearance and convenience operation.
- White color, graceful style and good adaptability to environment.
- Made of high quality ABS, anti-collision, flame retardant, resistance to impact. All the materials complied with ROHS standard.
- Removable adapter mounting seat.
- SC simplex, LC duplex and SC duplex adapters available, up to 4 cores.
- Ability to allow drop cables to enter from front, side or rear of the box.



Product Details



2 x LC Duplex Adapters, 4 Fibers

2 x SC Duplex Adapters, 4 Fibers

Specifications

Working Temperature	-25~+60°C	Storage Temperature	-40~+70°C
Humidity	93%(+30°C)	Air Pressure	70KPa~106KPa
Size (W×H×D) mm	122 x 81 x 22	Weight (kg)	0.07
Color	White	Material	ABS
Capacity (Cores)	1, 2, 4	Installation Models	Desktop or Wall Mounted
Number of Outlets	2	Number of Cable Entre Points	3
Connect Models	Fusion splicing	Drop Cable (Flat)	Indoor Flat Drop cable 2mm×3mm
Drop Cable (Round)	≤Φ10mm	Curvature Radius (mm)	≥30

Ordering Sample

Part Number	Description
PTB012-01E	1 port PTB012 type termination box, without adapter and pigtail.
PTB012-01FSPBLG652D05	1 port PTB012 type termination box with simplex SC/PC adapters and 0.5M singlemode SC/PC pigtails.