

Sales Catalog of HNK Telecommunication Products

Splicing & Engineer Accessories

Fiber optic Splice Tray (FST-24P)

This fiber optic splice tray is used for optical fiber storage and fiber optic fusion protection, easy to operate and simple to install and uninstall. Several trays are used together to splice a large fiber cable. The fiber splice trays can be used one on top of another to form a layer structure inside the fiber optic enclosures. 24 cores available.



Standards Compliance

- TIA/EIA 568.C (Optical Fiber Cabling Components Standard).
- ISO/IEC 11801(Generic cabling for customer premises).
- IEC 61073-1, Mechanical splices and fusion splice protectors for optical fibers and cables.
- EN50173 (Telecommunications Infrastructure Standard for Data Centres).
- 2011/65/EU (ROHS2.0, Directive on Restriction of Hazardous Substances.).

Features

- Center holes for mounting of the tray.
- Multiple tie down holes for securing incoming fiber.
- Designed for swing-up, installed 1 by 1.
- Removable splice holders module, min PLC splitter holders module.
- Storage and protect splice fibers, reach up to max 24 fibers.
- Scientific design with large bent radius, simple to install and operate.
- Durable ABS material used for long time; repeatable operation.
- Accommodate standard heat shrink sleeves in 40~60mm lengths with 2.5 mm diameter.
- Installable in wall mount & slidable patch panel & splice closures



Specification

Part Number	FST-24P
Dimension (L x W x H)	161 x 108 x 13 mm
Body Material and Cover	ABS
Transparent lid	Plastic
Body Color	White
Splice Capacity	24 Fibers
Operating Temperature	-40°C to +60°C

Ordering Information

Part Number	Description
FST-24P	24 Cores Splicing Tray.