

Sales Catalog of HNK Telecommunication Products
Fiber Optic Splice Closure

Horizontal Inline Fiber Optic Splice Closure (FOSC- H002)

The horizontal inline fiber optic splice closure is suitable for protecting fiber cable splices in straight through and branching applications. Its well-engineered, injection molded high-quality ABS outer body makes it impenetrable to the elements. Fiber optical splice closures are not only ideal suit for the long-term use in areas with great surface temperature differences or strong UV light, but also applicable for the directly buried installation in dry areas or long-term water-free manholes.



Features

- To adopt high-quality ABS make the closure has longer life time.
- The case body and cable entrance are sealed with silicone rubber sealing ring and insulation tape.
- The external component and fastening piece are all made of the high-quality stainless steel.
- The sealing structure keep good sealing performance after re-entry and re-using.
- The closure is spacious enough for winding and storing fibers.
- Unique configuration of the plug to cover unused inlets.
- Splice trays are easy to insert and remove, can accommodate 4 splice trays.

Specifications

Working Temperature	-25~+60°C	Storage Temperature	-40~+70°C
Humidity	93%(+30°C)	Air Pressure	70KPa~106KPa
Size (L×W×H) mm	460*180*110	Weight (kg)	3
Color	Black	Material	ABS (ROHS standard)
Max. Capacity (Per Tray)	24 Fibers	Max. Capacity of Splice Trays	4
Max. Capacity (Cores)	96	Cables Entry & Exit	4 Ports
Suitable for Cable Diameter	Φ7-Φ18mm	Curvature Radius (mm)	≥30
Protective Level	IP65	Sealing Method	silicone rubber sealing ring and insulation tape